

Scrubber driers

CT15 / CT30 / CT45



Features

- Solution distribution from brush center
- Solution control (solenoid valve)
- Brush control with soft start
- CFS (Center Flow System)
- Great manoeuvrability thanks to an optimum weight distribution
- Battery level indicator
- Tanks and surroundings body in high density polyethylene
- Squeegee system designed to absorb harsh impact
- Brush replacement without tools
- Squeegee blade can be used on 4 sides before replacement



The recovery tank can be removed simply without tools to help the operations of dirty water drain and have an easy access to internal compartments.



It is possible to adjust the handlebar height during work to ease the cleaning operations in difficult to reach areas.



The control panel, easy to use and intuitive, allows to activate the brush, the vacuum motor and water supply.

Code	Model	Scrubbing width (mm)	Suction width (mm)	Productivity (m ² /h)	No. of brushes	Solution tank capacity (l)	Recovery tank capacity (l)	Power supply	Max speed (km/h)	Weight (net) (kg)	Dimensions (LxWxH) (cm)
LPTB01229	CT15 B 35	350	450	1225	1 (disc)	16	19	24V (2x12V)	3.5	36	395x740x535
LPTB00517	CT15 C 35	350	450	1225	1 (disc)	16	19	220-240V (50Hz)	3.5	36	395x740x535
LPTB01523	CT30 B 45	450	550	1575	1 (disc)	28	30	24V (2x12V)	3.5	48	960x550x1220
LPTE00531	CT30 C 45	450	550	1575	1 (disc)	28	30	230V (50Hz)	3.5	48	960x550x1220
LPTB01520	CT45 B 50	500	730	1750	1 (disc)	40	45	24V (2x12V)	3.5	55	821x576x1220
LPTB01103	CT45 C 50	500	730	1750	1 (disc)	40	45	230V (50Hz)	3.5	55	821x576x1220