

Scrubber driers

CT160 / CT230



Features

CT160


- Brush control with automatic “delayed” stop
- SLS (Self Levelling System)
- High quality and performance vacuum motor
- Brush head designed to absorb harsh impact
- Huge solution tank capacity in minimum external space
- Great manoeuvrability thanks to an optimum weight distribution
- Great visibility whilst working

CT230

- Extensive running time
- SLS (Self Levelling System)
- Huge tank capacity in minimum external space. 205-225 litre capacity tanks make this model very unique in its category
- SLS (Self Levelling System)
- Automatic brush pressure control
- Squeegee system designed to absorb harsh impact



Pre-programmed working settings.



Water level control on both tanks. Maximum protection for the vacuum motor (Water Level Sensor).



Extensive running time. Extremely large battery compartment allows batteries of up to 320 Ah (4.5 running time).

Code	Model	Scrubbing width (mm)	Suction width (mm)	Productivity (m ² /h)	No. of brushes	Solution tank capacity (l)	Recovery tank capacity (l)	Power supply	Max speed (km/h)	Weight (net) (kg)	Dimensions (LxWxH) (cm)
LPTB01331	CT160 BT 70	700	830	4550	2 (disc)	145	170	36V	6.5	273	1720x850x1360
LPTB01332	CT160 BT 85	850	1010	5525	2 (disc)	145	170	36V	6.5	290	1720x1010x1360
LPTB01333	CT160 BT 95	950	1100	6175	2 (disc)	145	170	36V	6.5	292	1720x1010x1360
LPTB02038	CT230 BT 85	850	1010	5525	2 (disc)	205	225	36V	6.5	350	1950x935x1466
LPTE02045	CT230 BT 105	1050	1280	6825	2 (disc)	205	225	36V	6.5	377.5	1950x1155x1466