


Scrubber driers

CT40 / CT55 / CT70



Features

- Solution distribution from brush center
- CWS (Constant Weight System)
- Exclusive squeegee system assures high performance at low cost
- Great manoeuvrability thanks to an optimum weight distribution
- Design to assure minimum noise levels
- Recovery tank discharge point and hose at maximum height
- Brush replacement without tools
- Squeegee blade can be used on 4 sides before replacement
- AFS (Anti Foam System)
- Battery level indicator



Water level control on both tanks. Maximum protection for the vacuum motor (Water Level Sensor).



Brush control with automatic delayed stop saves brush wear and protects delicate surfaces. Brush rotation stops (3 sec delayed) and starts upon brush command.



Recovery tank can be tilted. Easy to rinse and clean thanks also to smooth internal finishes.

Code	Model	Scrubbing width (mm)	Suction width (mm)	Productivity (m ² /h)	No. of brushes	Solution tank capacity (l)	Recovery tank capacity (l)	Power supply	Max speed (km/h)	Weight (net) (kg)	Dimensions (LxWxH) (cm)
LPTB00546	CT40 C 50	500	815	1750	1 (disc)	40	50	220-240V 50Hz	3.5	83	1230x516x960
LPTB01406	CT40 B 50	500	815	1750	1 (disc)	40	50	24V (2x12V)	3.5	67	1230x516x960
LPTB01408	CT40 BT 50	500	815	2250	1 (disc)	40	50	24V (2x12V)	4.5	73	120x516x960
LPTB01516	CT55 B 55	550	815	1925	1 (disc)	55	60	24V (2x12V)	3.5	68.5	1190x640x1018
LPTE01102	CT55 C 55	550	815	1925	1 (disc)	55	60	230V 50Hz	3.5	83	1190x640x1018
LPTB01414	CT70 B 55	550	815	1925	1 (disc)	70	75	24V (2x12V)	3.5	84.5	1230x587x960
LPTB01416	CT70 BT 55	550	815	2475	1 (disc)	70	75	24V (2x12V)	4.5	91.5	1230x587x960
LPTB01417	CT70 BT 60	600	815	2700	2 (disc)	70	75	24V (2x12V)	4.5	93.7	1210x680x960
LPTB01418	CT70 BT 70	700	1010	3150	2 (disc)	70	75	24V (2x12V)	4.5	94.5	1220x748x960
LPTB01419	CT70 BT 85	800	1010	3600	2 (disc)	70	75	24V (2x12V)	4.5	95	1260x893x960