

Scrubber driers

CT70 Rider / CT110



Features

CT70 Rider

- Solution distribution from brush center
- CWS (Constant Weight System)
- AFS (Anti Foam System)
- Tanks and surroundings body in high density polyethylene
- Battery level indicator
- Great visibility whilst working
- Designed to assure minimum noise levels

CT110

- Huge tank capacity in minimum external space
- High quality and performance vacuum motor
- Inlet and outlet filters for solution tank protection
- Brush replacement without tools
- Squeegee designed to absorb harsh impact
- 3 solution distribution options: standard, automatic, economy



Exclusive squeegee system assures high performance at low cost.



Water level control on both tanks. Maximum protection for the vacuum motor (Water Level Sensor).



Easy access to internal compartment.

Code	Model	Scrubbing width (mm)	Suction width (mm)	Productivity (m ² /h)	No. of brushes	Solution tank capacity (l)	Recovery tank capacity (l)	Power supply	Max speed (km/h)	Weight (net) (kg)	Dimensions (LxWxH) (cm)
LPTB02400	CT70 Rider BT 60	600	815	2700	2 (disc)	70	75	24V (2x12V)	4.5	100	1395x671x960
LPTB02401	CT70 Rider BT 70	700	1010	3150	2 (disc)	70	75	24V (2x12V)	4.5	102	1395x748x960
LPTB01312	CT110 BT 60	600	815	3900	2 (disc)	110	115	24V / 280 Ah	6.5	209	1504x722x1201
LPTB01311	CT110 BT 70	700	940	4550	2 (disc)	110	115	24V / 280 Ah	6.5	214	1504x759x1201
LPTB01313	CT110 BT 85	850	1010	5525	2 (disc)	110	115	24V / 280 Ah	6.5	231	1504x909x1201