

Cold water high pressure washers

PW-C25



Standard accessories



TBAP28305
8 m hose with screw
coupling




IPPR40010
Trigger gun with
heatproof extensions
and swivel coupling



LCPR40046
Lance with adjustable
head

Features

- Asynchronous motor, 2-pole (2800 rpm), class S1 (continuous duty)
- IPC pump with separate By Pass, complete with pressure adjustment knob to adapt the pressure to the surface to be washed. The motor and the pump are mounted horizontally, while the structure is vertical. This improves the stability and manoeuvrability of the machine, which also occupies less space, even when stored, maintaining the natural working position of the pump-motor group at all times
- Professional pressure gauge to monitor work pressure at all times
- Strong structure that is resistant to thermal shocks, atmospheric agents and chemical corrosion
- Lance support as standard



The starting handgrip, the detergent tap and the inlet water connection are placed on the front side of the machine.



Removable transparent cover for an easy and rapid maintenance.



Standard supports for gun, lance and lance with rotating nozzle to have them ready to be used.



Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Voltage (Ph-V-Hz)	Absorbed power (kW)	Motor (HP)	RPM	Detergent tank (l)	Weight (kg)	Dimensions (cm)
IDAF94169	PW-C25 I 1813P-T	Total Stop	180	800	3-400-50	5	5.5	2800	3	30	48x40x93