

Hot water high pressure washers

PW-H25



Standard accessories



TBAP25324
H.P. flexible hose 10 m



IPPR40010
Handgun



LCPR12983
Double lance Inox P70



UGLN49991
Nozzle for lance

Optional accessories



LCPR29362
Hydro brush lance



SPID24939
Fixed hydro brush lance



LCPR24937
Foam head



TBAP23853
Drain kit 10 m



KTRI29366
Plunged ejector device



KTRI29377
Feeding kit



Lances for washing floors

Features

- Low pressure detergent delivery controlled from lance
- Pressure adjustment and steam knob accessible from outside, allowing pressure to be adapted to various cleaning situations
- Crankshaft pump with brass head and ceramic pistons
- Pressure gauge to monitor work pressure at all times
- Lance holder and H.P. hose support
- Thanks to the numerous accessories, including

- trigger gun with heatproof extension, 70 cm double stainless steel lance with pressure control device and detergent control, 10 m high pressure and temperature hose
- The safety level is guaranteed by: adjustable thermostat to modulate and limit water temperature; automatic pressure switch; safety valve to limit possible overpressure
- Simple electric panel complete with ON/OFF and output water temperature adjustment knob




Sturdy ergonomic handle for convenient easy manoeuvring.



Sturdy structure, shockproof, resistant to thermal shock and atmospheric agents.



The 4 large diameter wheels make the machine stable and facilitate movement on all surface (concrete, dirt tracks, gravel, etc.).



Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Voltage (Ph-V-Hz)	Absorbed power (kW)	Motor (HP)	RPM	Detergent tank (l)	Weight (kg)	Dimensions (cm)
IDAC40346	PW-H25 D1110P M	Total Stop D	40÷110	300÷600	1-230-50	2.7	2.5	2800	10	95	96x66x88
IDAC40347	PW-H25 D1813P T	Total Stop D	40÷180	390÷780	3-400-50	5.3	5.5	2800	10	95	96x66x88

For the D1110P M model, the output water temperature is 70÷120°C. For the D1813P T model, the output water temperature is 65÷120°C.